

Technical Manual



**01.003.01**

**REMOVE AND INSTALL  
FORK PROTECTOR**

**STARK FUTURE**



## SAFETY WARNINGS

Observe your local health and safety guidelines. Ensure a safe working environment. Wear appropriate protective gear. Deviating from the prescribed order may result in injury or damage to the products.



## TOOLS

- TRX 30
- TRX 25



## OPERATION TIME

10 Minutes

# REMOVAL



## WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.



## NOTE

Step 1 only for the left side fork protector. Skip step 1 for the right side fork protector.

- 1 Remove the front line bracket.  
Refer to:



## 02.011.01

Remove and Install front brake line bracket ↗.

- 2 Unscrew the fork protector bolts.
- 3 Remove the fork protector.

# 3

# INSTALLATION



## WARNING

Before proceeding with any work on the bike, make sure it is turned off and the charger disconnected.

- 1 Hold the fork protector in place.
- 2 Tighten all fork protector bolts by hand.
- 3 Tighten the 3x bolts to **10 Nm**.

## NOTE



Step 4 only for the left side fork protector. Skip step 4 for the right side fork protector.

- 4 Install the front brake line bracket.  
Refer to:



## 02.011.01

Remove and Install front brake line bracket ↗.



## WARNING

Check brakes operation before operating the bike.

starkfuture.com

ENG 2023-06

Copyright © 2023 Stark Future SL. All rights reserved.  
Reproduction, even in part, as well as copying of all kinds,  
is permitted only with the express written permission  
of the copyright owner.

**STARK FUTURE**